

REVOX DOT-4 LV BRAKE FLUID

PRODUCT DESCRIPTION

Revox Brake Fluid DOT-4 LV is a highly efficient brake fluid which is a combination of high quality glycols, glycol ethers, metal corrosion inhibitors and anti-oxidants

Due to its high boiling point, Revox Brake Fluid DOT-4 LV performs outstanding at the high operating temperature of the brake system and prevents vapour lock. In addition, it delivers excellent anti-corrosion properties to protect the braking system and seals.

In particular, Revox Brake Fluid DOT-4 LV is recommended for vehicles with the latest generation electronic control safety systems for braking and stability (ABS, ESP/ESC), it also features a very low viscosity.



APPLICATIONS

- Automobile manufacturing line
- All models with hydraulic brake system

Important notice: The manufacturers' instructions should always be followed

PROPERTIES

- High boiling point and wet boiling point (prevent Vapor lock)
- Low kinematic viscosity and proper lubrication performance at low temperature
- Superior metal corrosion protection
- Rubber compatibility (SBR, EPDM Rubber)
- Excellent low temperature stability and thermal stability

SPECIFICATIONS & APPROVALS

KS M 2141 Type 6; FMVSS 116 DOT-4; SAE J1704 (Low Viscosity); ISO 4925 Class 6; JIS K 2233 Type 6 (BF-6)

TECHNICAL DATA

Parameter	Unit	Result
Density at 20°C	g/cm ³	1.06~1.07 m
pH		7.0 ~ 8.5
Boiling Point Dry	°C	Min 265
Boiling Point Wet	°C	Min 175
Viscosity @ -40°C	mm ² /s	Max 750
Viscosity @ 100°C	mm ² /s	Min 1.5