



REVOX 0W-30 SP/C3

PRODUCT DESCRIPTION

Revox 0W30 SP/C3 is a low-ash (SAPS) high-fuel-efficiency, high-performance, 100% synthetic engine oil optimized for passenger vehicles equipped with exhaust gas purification aftertreatment devices (DPFs).

Its strong oxidation stability suppresses sludge formation and friction-induced wear, providing enhanced engine protection.



APPLICATIONS

- Passenger diesel and gasoline engine vehicles equipped with DPFs/TWCs
- Optimal lubrication performance even under demanding driving conditions (city driving, general roads, and highways)

Important notice: The manufacturers' instructions should always be followed

SPECIFICATIONS & APPROVALS

API SP; ACEA C3

PROPERTIES

- Minimizes power loss in high-temperature environments, resulting in outstanding fuel economy.
- Low volatility and high oxidation stability to minimize engine oil consumption
- State-of-the-art additives to maintain peak performance of the exhaust gas reduction devices, such as DPFs and TWCs
- Special friction and wear reducing agents reduce noise





TECHNICAL DATA

Parameter	Test Method	Unit	Result
Viscosity Grade	SAEJ 300	-	0W-30
Density at 15°C		g/cm ³	0.843
Viscosity @ 40°C	ASTM D445	mm ² /s	58.4
Viscosity @ 100°C	ASTM D445	mm ² /s	10.8
Viscosity Index	ASTM D2270	-	175
Flash Point		°C	236
Pour Point		°C	-45
CCS		mPa·s	5,180

