

REVOX PREMIUM LONGLIFE COOLANT

PRODUCT DESCRIPTION

REVOX PREMIUM LONG LIFE COOLANT is a ready-to-use coolant based on ethylene glycol with state-of-the-art P-OAT corrosion protection technology. This product does not contain amine, borate, silicate and nitrite.

REVOX PREMIUM LONG LIFE COOLANT maintains anti-corrosion performance and is effective in preventing cavitation corrosion that may occur in aluminum engine heads and engine blocks. This product has been supplied to the production line and genuine parts of HYUNDAI · KIA Motors for a long time.

The recommended drain interval is 5 years or 200,000km, whatever comes first.



APPLICATIONS

- Production line of car makers, such as KIA, HYUNDAI Motors
- Industrial cooling system, vessel refrigerator system

Important notice: The manufacturers' instructions should always be followed

PROPERTIES

- Outstanding hot surface aluminum protection
- Superior protection in high operating temperatures
- Improve water pumpability due to reduced water pump seal wear
- Excellent long-term corrosion protection

SPECIFICATIONS & APPROVALS

HYUNDAI·KIA Motors MS 591-08, Mitsubishi Motors ES-X64217, Mazda Motors MES MN 121K, Korea Standard KS M 2142, Chinese Standard GB 29743, ASTM Standard ASTM D3306, Japanese Standard JIS K 2234

TECHNICAL DATA

Parameter	Test Method	Unit	Result
pH	ASTM D1287	-	8.2
Density at 20°C	ASTM D1122	g/ml	1.134
Colour	VISUAL	-	Pink
Freezing point °C	ASTM D1177	°C	-36°C
Boiling point °C	ASTM 1120	°C	168
Water content	ASTM D1123	% wt/wt	4.6